



PRICE LIST

Ref No. RRKL/LP/BCISI/10-1/24
w.e.f. 11th October 2024

THE ONLY INDIAN
WIRE BRAND
TRUSTED BY

90+

COUNTRIES
GLOBALLY



RR KÄBEL
WIRES & CABLES

**AKALMAND BANO,
SAHI CHUNO.**

AKALMAND BANO, SAHI CHUNO.



BUILDING WIRES

RR KÄBEL
WIRES & CABLES

INDIA'S ONLY WIRE WITH
REACH • RoHS
CE • CPR Compliant



SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 0.75 | 24/0.2 | 1453 | 24 |
| 1.0 | 14/0.3 | 1981 | 24 |
| 1.5 | 22/0.3 | 2887 | 16 |
| 2.5 | 36/0.3 | 4621 | 12 |
| 4.0 | 56/0.3 | 6733 | 8 |
| 6.0 | 84/0.3 | 10032 | 4 |

UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand flexible High Conductivity plain annealed copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 1.0 | 37/0.19 | 2075 | 24 |
| 1.5 | 37/0.23 | 3016 | 16 |
| 2.5 | 61/0.23 | 4836 | 12 |
| 4.0 | 61/0.29 | 7387 | 8 |
| 6.0 | 91/0.29 | 10981 | 4 |

FIREX LSOH HALOGEN FREE FLAME RETARDANT 90°C, CROSSLINKED



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, Cross linked Halogen Free Flame Retardant (HFFR) 90° C Insulated Industrial Cables in voltage grade upto and including 1100 volts, as per IS 17048 (HSN Code: 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 1.00 | 14/0.3 | 2439 | 24 |
| 1.50 | 22/0.3 | 3436 | 16 |
| 2.50 | 36/0.3 | 5443 | 12 |
| 4.00 | 56/0.3 | 7988 | 8 |
| 6.00 | 84/0.3 | 11570 | 4 |

* FIREX LSOH - Insulation Conforming to HFI XL 90 as per IS 17048

RR KABEL FR HSF / FR-LSH



 RR KABEL

RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

| RATE / 200 MTR | | | | | |
|----------------|---------------|------|--------------------------------------|--|--|
| Size (Sq.mm) | Configuration | AMPS | RR KABEL FR HSF FR PVC INSULATION | RR KABEL FR-LSH FR-LSH PVC INSULATION | No. of Coils packed in an Outer Box |
| 0.75 | 24/0.2 | 8 | 3494 | 3613 | 12 |
| 1.0 | 32/0.2 | 13 | 4562 | 4722 | 12 |
| 1.5 | 30/0.25 | 17 | 6597 | 6823 | 8 |
| 2.5 | 50/0.25 | 24 | 10740 | 11118 | 6 |
| 4.0 | 56/0.3 | 30 | 16511 | 17091 | 4 |
| 6.0 | 84/0.3 | 38 | 24555 | 25352 | 2 |

LSOH-FR



 RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper Thermoplastic Halogen Free Flame Retardent (HFFR) 70° C Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 17048 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | AMPS | Unit | Rate | No. of Coils packed in an Outer Box |
|--------------|---------------|------|---------|-------|---|
| 0.75 | 24/0.2 | 8 | 180 Mtr | 3482 | 12 |
| 1.0 | 32/0.2 | 13 | 180 Mtr | 4388 | 12 |
| 1.5 | 30/0.25 | 17 | 180 Mtr | 6173 | 8 |
| 2.5 | 50/0.25 | 24 | 180 Mtr | 9990 | 6 |
| 4.0 | 56/0.25 | 30 | 180 Mtr | 15318 | 4 |
| 6.0 | 84/0.3 | 38 | 180 Mtr | 22713 | 2 |

FR HSF



 RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper FR PVC Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | AMPS | Unit | Rate | No. of Coils packed in an Outer Box |
|--------------|---------------|------|---------|-------|---|
| 0.75 | 24/0.2 | 8 | 180 Mtr | 2944 | 12 |
| 1.0 | 32/0.2 | 13 | 180 Mtr | 3847 | 12 |
| 1.5 | 30/0.25 | 17 | 180 Mtr | 5562 | 8 |
| 2.5 | 50/0.25 | 24 | 180 Mtr | 9077 | 6 |
| 4.0 | 56/0.25 | 30 | 180 Mtr | 13889 | 4 |
| 6.0 | 84/0.3 | 38 | 180 Mtr | 20650 | 2 |



COMMUNICATION CABLES

RR KĀBEL
WIRES & CABLES

- RATNA CO-X
- RATNA LAN
- RATNA COM
- CCTV CAMERA CABLE
- SPEAKER CABLE

RATNA CO-X



RR Kabel makes Electrolytic grade solid annealed bare copper conductor gas injected physical polyethylene foam insulated, wrapped with Aluminium Mylar tape and Al alloy wire braided, Jelly flooded and PVC Jacketing in Black Colour, Co-Axial Industrial Cables. (HSN Code : 8544)

| RG 59 F | | RG 6 F | | RG 11 F | |
|---------|----------|---------|----------|---------|----------|
| 90 Mtr. | 305 Mtr. | 90 Mtr. | 305 Mtr. | 90 Mtr. | 305 Mtr. |
| 2207 | 7485 | 2824 | 9565 | 6289 | 21316 |

RATNA LAN



RR Kabel makes Solid bare copper conductor 4 Pair unshielded twisted pair (UTP) Industrial cables for Computer Lan Network with Grey colour & FR PVC Jacket. (HSN Code : 8544)

| CAT 5e | | CAT 6 | |
|----------|----------|----------|----------|
| 100 Mtr. | 305 Mtr. | 100 Mtr. | 305 Mtr. |
| 3525 | 10744 | 4709 | 14365 |

RATNA COM



RR Kabel makes Solid Electrolytic annealed bare copper conductor Industrial Switchboard & Telephone Cables with high density polyethylene insulation, paired, polyester taped, Nylon Rip Cord and Grey colour sheathed with FR PVC, generally conform to "ITD specification S/WS 113 C" (HSN Code : 8544) (Rate/90 Mtr Coil)

| Dia | 1 Pair | 2 Pair | 3 Pair | 4 Pair | 5 Pair | 10 Pair | 20 Pair |
|--------|--------|--------|--------|--------|--------|---------|---------|
| 0.5 mm | 1023 | 1800 | 2651 | 3476 | 4331 | 8275 | 15708 |

CCTV CAMERA CABLES



RR Kabel makes Annealed Tinned copper conductor, PE Insulated, ATC Braided, Polyester tape screened, PVC outer sheathed Industrial CCTV Camera Cables.(HSN CODE : 8544)

| Size | Packing | Rate Per Coil | No. of Coils packed in an Outer Box |
|-------|---------|---------------|-------------------------------------|
| 3 + 1 | 90 Mtr. | 4202 | 3 |
| 4 + 1 | 90 Mtr. | 4709 | 3 |

SPEAKER CABLES



RR Kabel makes Multistrand Annealed bare copper conductor, PVC Insulated Industrial Speaker wires. (HSN CODE : 8544)

| Size | Packing | Non Transparent Insulation (Rate/Coil) | Transparent Insulation (Rate/Coil) | No. of Coils packed in an Outer Box |
|-----------|---------|--|------------------------------------|-------------------------------------|
| 2C x 0.50 | 90 Mtr. | 2048 | 2109 | 10 |
| 2C x 0.75 | 90 Mtr. | 2920 | 3008 | 10 |
| 2C x 1.0 | 90 Mtr. | 3679 | 3789 | 8 |
| 2C x 1.5 | 90 Mtr. | 5309 | 5468 | 8 |
| 2C x 2.5 | 90 Mtr. | 8455 | 8709 | 8 |



INDUSTRIAL CABLES

RR KÄBEL
WIRES & CABLES

- FLEXIBLE SINGLE CORE CABLE
- FLEXIBLE MULTICORE CABLES
- SHIELDED CABLE
- BRAIDED CABLE

RR KABEL FR HSF / FR-LSH / LSOH-FR



RR Kabel makes single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code : 8544)

| RATE / 100 MTR | | | | | |
|----------------|---------------|------|---|---|---|
| Size (Sq.mm) | Configuration | AMPS | RR KABEL FR HSF FR PVC INSULATION As Per IS 694 | RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694 | RR KABEL LSOH-FR <small>Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048</small> |
| 10.0 | 140/0.3 | 52 | 21558 | 22309 | 23684 |
| 16.0 | 126/0.4 | 70 | 34123 | 35313 | 37300 |
| 25.0 | 196/0.4 | 88 | 55108 | 57313 | 61724 |
| 35.0 | 276/0.4 | 112 | 77088 | 80171 | 86336 |
| 50.0 | 396/0.4 | 146 | 109935 | 114330 | 123125 |
| 70.0 | 360/0.5 | 216 | 155796 | 162028 | 174489 |
| 95.0 | 480/0.5 | 262 | 209581 | 217964 | 234730 |
| 120.0 | 608/0.5 | 310 | 271181 | 282032 | 303725 |
| 150.0 | 750/0.5 | 355 | 336164 | 349614 | 376503 |
| 185.0 | 931/0.5 | 415 | 408840 | 425195 | 457898 |
| 240.0 | 1200/0.5 | 500 | 537864 | 559377 | 602407 |
| 300.0 | 1500/0.5 | 550 | 671470 | 698331 | 752046 |
| 400.0 * | 2013/0.5 | 590 | 912436 | 948935 | 1021928 |
| 500.0 * | 2562/0.5 | 660 | 1182734 | 1230041 | 1324660 |
| 630.0 * | 3416/0.5 | 725 | 1572198 | 1635085 | 1760862 |

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

** RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

RR KABEL FR HSF SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | AMPS | Rate Per 100 Mtr |
|--------------|---------------|------|------------------|
| 0.5 | 16/0.2 | 5 | 1236 |
| 0.75 | 24/0.2 | 8 | 1737 |
| 1.0 | 32/0.2 | 13 | 2264 |
| 1.5 | 30/0.25 | 17 | 3274 |
| 2.5 | 50/0.25 | 24 | 5333 |
| 4.0 | 56/0.3 | 30 | 8153 |
| 6.0 | 84/0.3 | 38 | 12129 |

RATNA FLEX MULTICORE CABLES



RR Kabel makes Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Rate per 100 meter | | | | | | | | | | | |
|--------------------|---------|------|--------|--------|--------|--------------|----------|------|--------|---------|---------|
| Size (Sq.mm) | CONFIG. | AMPS | 2 CORE | 3 CORE | 4 CORE | Size (Sq.mm) | CONFIG. | AMPS | 2 CORE | 3 CORE | 4 CORE |
| 0.5 | 16/0.2 | 5 | 3534 | 4664 | 5864 | 25.0 | 196/0.4 | 88 | 124855 | 177002 | 233200 |
| 0.75 | 24/0.2 | 8 | 4654 | 6269 | 8010 | 35.0 | 276/0.4 | 112 | - | 247178 | 327548 |
| 1.0 | 32/0.2 | 13 | 5703 | 7964 | 10197 | 50.0 | 396/0.4 | 146 | - | 352844 | 459503 |
| 1.5 | 30/0.25 | 17 | 7880 | 10891 | 14179 | 70.0 | 360/0.5 | 216 | - | 496424 | 654435 |
| 2.5 | 50/0.25 | 24 | 12475 | 17472 | 22724 | 95.0 | 480/0.5 | 262 | - | 669665 | 878074 |
| 4.0 | 56/0.3 | 30 | 19165 | 26881 | 35217 | 120.0 | 608/0.5 | 310 | - | 845420 | 1119669 |
| 6.0 | 84/0.3 | 38 | 27629 | 39409 | 51854 | 150.0 | 750/0.5 | 355 | - | 1073143 | 1407532 |
| 10.0 | 140/0.3 | 52 | 48582 | 69610 | 90710 | 185.0 | 931/0.5 | 415 | - | 1318665 | 1712382 |
| 16.0 | 126/0.4 | 70 | 75899 | 107193 | 141243 | 240.0 | 1200/0.5 | 500 | - | 1713790 | 2315857 |
| | | | | | | 300.0 | 1500/0.5 | 550 | - | 2137762 | 2892719 |

CONTROL CABLES



RR Kabel makes Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

| Rate per 100 meter | | | | | | | | | | | | |
|--------------------|---------|------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Size (Sq.mm) | CONFIG. | AMPS | 5 CORE * | 6 CORE * | 7 CORE * | 8 CORE * | 10 CORE * | 12 CORE * | 14 CORE * | 16 CORE * | 19 CORE * | 24 CORE * |
| 0.5 | 16/0.2 | 5 | 7905 | 9225 | 10282 | 12206 | 15142 | 17786 | 20603 | 23111 | 27268 | 34908 |
| 0.75 | 24/0.2 | 8 | 10785 | 12971 | 14537 | 17434 | 21315 | 25353 | 29445 | 33587 | 40498 | 50724 |
| 1.0 | 32/0.2 | 13 | 13771 | 16142 | 18381 | 21894 | 27286 | 32066 | 37560 | 42113 | 51921 | 63900 |
| 1.5 | 30/0.25 | 17 | 19260 | 22866 | 26160 | 30679 | 38411 | 45338 | 52788 | 59456 | 70349 | 90135 |
| 2.5 | 50/0.25 | 24 | 30697 | 37219 | 42644 | 49452 | 62308 | 73376 | 86073 | 98387 | 117014 | 146891 |
| 4.0 | 56/0.3 | 30 | 47676 | 58041 | 67057 | 78971 | 98700 | 116919 | 136170 | 155195 | 183339 | 234243 |
| 6.0 | 84/0.3 | 38 | 71045 | 85975 | 100198 | 115915 | 148114 | 175566 | 203508 | 231793 | 273522 | 348992 |
| 10.0 | 140/0.3 | 52 | 121386 | - | - | - | - | - | - | - | - | - |
| 16.0 | 126/0.4 | 70 | 191275 | - | - | - | - | - | - | - | - | - |

Loading factor for Different Insulation / Sheath * -

| FR Insulation | FR Sheath | FR-LSH / HR Insulation | FR-LSH / HR Sheath | LSOH Insulation | LSZH Sheath |
|---------------|-----------|------------------------|--------------------|-----------------|-------------|
| 5% | 5% | 10% | 10% | 35% | 25% |

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

SUBMERSIBLE FLAT CABLES

RR Kabel makes 3 Core PVC Insulated and sheathed Industrial Flat cables for Submersible Motor, working voltages upto and including 1100 Volts, as per IS 694



| Size (Sq.mm) | Configuration | Rate 100 mtr |
|--------------|---------------|--------------|
| 1.5 | 22/0.3 | 11640 |
| 2.5 | 36/0.3 | 18150 |
| 4.0 | 56/0.3 | 26608 |
| 6.0 | 84/0.3 | 38586 |
| 10.0 | 140/0.3 | 67185 |
| 16.0 | 126/0.4 | 104195 |
| 25.0 | 196/0.4 | 163655 |

* For XLPE Insulated Submersible Flat Cables (Cu/XLPE/PVC), contact us for pricing and availability. MOQ will be applicable.

ONLY THE BEST SUBMERSIBLE CABLES CAN WITHSTAND THE HARSHTEST CONDITIONS.

- PVC & XLPE Insulation
- Electrolytic Grade
Annealed Copper
- Better Conductivity
- CE, REACH &
RoHS Compliant



AKALMAND BANO, SAHI CHUNO.

SHIELDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

| SIZE | Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | MOQ (KM) |
|---------|---|-------|-------|-------|--------|----------|
| | 0.50 | 0.75 | 1.00 | 1.50 | 2.50 | |
| 2 Core | 6491 | 7873 | 9170 | 11729 | 17249 | 3 |
| 3 Core | 8125 | 10185 | 12104 | 15620 | 23976 | 3 |
| 4 Core | 10162 | 12896 | 15486 | 20441 | 30922 | 3 |
| 5 Core | 11677 | 15144 | 18393 | 24640 | 38403 | 3 |
| 6 Core | 13645 | 17784 | 21889 | 28716 | - | 3 |
| 7 Core | 15137 | 19971 | 24452 | 32688 | 50317 | 3 |
| 8 Core | 17158 | 22738 | 27683 | 37451 | 59727 | 2 |
| 9 Core | 18970 | - | - | - | - | 2 |
| 10 Core | 21035 | 27970 | 34455 | 47269 | 74072 | 2 |
| 12 Core | 24369 | 32704 | 40854 | 55218 | 87817 | 2 |
| 14 Core | 27748 | 37106 | 47021 | 63826 | 102922 | 1 |
| 16 Core | 31470 | 43101 | 53142 | 72356 | 117467 | 1 |
| 18 Core | 34944 | 47548 | 59317 | 80869 | 132552 | 1 |
| 20 Core | 38643 | 52138 | 65796 | 92612 | 147049 | 1 |
| 22 Core | 42551 | 57552 | 72007 | - | - | 1 |
| 25 Core | 47728 | 64775 | 81964 | - | - | 1 |
| 27 Core | 51141 | 69534 | 87243 | - | - | 1 |

Note : Please contact to HO for Technical Data Sheet.

SHIELDED ARMoured CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor PVC / XLPE Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour And Outer PVC Sheathed Industrial Instrumentation (Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| SIZE | Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | MOQ (KM) |
|---------|---|-------|--------|--------|--------|----------|
| | 0.50 | 0.75 | 1.00 | 1.50 | 2.50 | |
| 2 Core | 12572 | 14582 | 16483 | 19783 | 26526 | 5 |
| 3 Core | 14992 | 17597 | 20499 | 24551 | 34354 | 5 |
| 4 Core | 17148 | 20546 | 24207 | 29471 | 43418 | 3 |
| 5 Core | 19671 | 23993 | 28572 | 34925 | 51001 | 3 |
| 6 Core | 21966 | 27183 | 32425 | 41077 | - | 3 |
| 7 Core | 23473 | 29165 | 34712 | 44855 | 67252 | 3 |
| 8 Core | 26721 | 32871 | 38780 | 50704 | 75455 | 3 |
| 9 Core | 28573 | - | - | - | - | 3 |
| 10 Core | 30692 | 38591 | 47245 | 62471 | 92824 | 3 |
| 12 Core | 34703 | 43788 | 53906 | 70615 | 108985 | 3 |
| 14 Core | 38478 | 49171 | 62679 | 81335 | 121511 | 3 |
| 16 Core | 43008 | 58037 | 67712 | 91523 | 137309 | 3 |
| 18 Core | 48479 | 59426 | 75697 | 101664 | 152770 | 3 |
| 20 Core | 54340 | 65696 | 82938 | 115563 | 169188 | 2 |
| 22 Core | 55552 | 71868 | 89850 | - | - | 2 |
| 24 Core | - | - | 96519 | - | - | 2 |
| 25 Core | 60834 | 79272 | 99532 | - | - | 2 |
| 27 Core | 63934 | 83702 | 110450 | - | - | 2 |

Note : Please contact to HO for Technical Data Sheet.

BRAIDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | |
|---|-------|-------|-------|-------|-------|--------|
| SIZE | 0.25 | 0.50 | 0.75 | 1.00 | 1.50 | 2.50 |
| 2 Core | 8573 | 9873 | 10718 | 12130 | 15468 | 22641 |
| 3 Core | 9224 | 11014 | 13313 | 15323 | 19995 | 29725 |
| 4 Core | 11090 | 13472 | 16495 | 19400 | 25014 | 38126 |
| 5 Core | 13890 | 15736 | 19747 | 23124 | 30567 | 47419 |
| 6 Core | 16362 | 17376 | 20894 | 26232 | 34325 | - |
| 7 Core | 17272 | 18864 | 24088 | 28952 | 38738 | 60263 |
| 8 Core | 18506 | 21278 | 26967 | 32973 | 44750 | - |
| 9 Core | - | - | - | - | 50065 | - |
| 10 Core | 22111 | 27029 | 34266 | 40829 | 55620 | - |
| 12 Core | 24502 | 29398 | 39304 | 47772 | 64786 | 100779 |
| 14 Core | - | 33678 | 44855 | 55266 | 75160 | - |
| 16 Core | - | 37910 | 50568 | 62205 | 84624 | - |
| 18 Core | 34481 | 41836 | 56681 | 69585 | 94531 | - |

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | |
|---|-------|-------|--------|--------|
| SIZE | 4.0 | 6.0 | 10.0 | 16.0 |
| 2 Core | 32687 | 45047 | - | - |
| 3 Core | 44874 | 62415 | - | - |
| 4 Core | 56493 | 79598 | 133628 | 216177 |

Note : Please contact HO for Technical Data Sheet.

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.

PAIR SHIELDED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|-------|--------|----------|--------|--------|--------|----------|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 1 | 7858 | 9624 | 10 | 11923 | 13733 | 19764 | 5 |
| 2 | 12872 | 15641 | 5 | 19958 | 24796 | 37159 | 3 |
| 3 | 16660 | 21031 | 3 | 26515 | 34971 | 52849 | 3 |
| 4 | 19377 | 27048 | 3 | 34038 | 44486 | 69040 | 3 |
| 5 | 23615 | 32974 | 3 | 42198 | 53917 | 82580 | 3 |
| 6 | 27557 | 38732 | 3 | 50246 | 63889 | 98175 | 2 |
| 8 | 35375 | 49801 | 3 | 63119 | 84498 | 129250 | 2 |
| 10 | 43541 | 60500 | 3 | 77687 | 103432 | 160225 | 2 |
| 12 | 51811 | 72301 | 3 | 92216 | 123104 | 191137 | 2 |
| 14 | - | - | - | - | 141212 | - | 1 |
| 16 | 67293 | 94543 | 2 | 122174 | 163761 | 255067 | 1 |
| 20 | 83570 | 117870 | 2 | 151248 | 203238 | 317139 | 1 |
| 24 | 99139 | 140230 | 2 | 180240 | 242604 | 379123 | 1 |

RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|--------|--------|----------|--------|--------|--------|----------|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 | 16704 | 19446 | 5 | 23820 | 29519 | 42111 | 2 |
| 3 | 21690 | 26980 | 5 | 33447 | 41254 | 59664 | 2 |
| 4 | 27698 | 33795 | 3 | 40635 | 53705 | 78095 | 2 |
| 5 | 32717 | 40994 | 3 | 50955 | 65186 | 95305 | 1 |
| 6 | 38874 | 49338 | 2 | 59741 | 77379 | 113412 | 1 |
| 8 | 51971 | 64378 | 2 | 78952 | 101702 | 149590 | 1 |
| 10 | 63867 | 79369 | 1 | 97520 | 125931 | 185666 | 1 |
| 12 | 75740 | 94313 | 1 | 116072 | 145867 | 221677 | 1 |
| 16 | 99993 | 121592 | 1 | 148565 | 194284 | 287577 | 1 |
| 20 | 123785 | 150761 | 1 | 186196 | 241544 | 357983 | 1 |
| 24 | 147553 | 179938 | 1 | 222395 | 288779 | 428363 | 1 |
| 25 | - | - | - | 231446 | - | - | 1 |

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

PAIR SHIELDED ARMOURED CABLES



RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire/Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Overall Pair Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|--------|--------|----------|--------|--------|--------|----------|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 1 | 12697 | 14582 | 10 | 16641 | 19783 | 26526 | 5 |
| 2 | 19492 | 23179 | 5 | 27126 | 33129 | 46251 | 3 |
| 3 | 22859 | 27458 | 3 | 32853 | 42766 | 63789 | 3 |
| 4 | 27642 | 34021 | 3 | 40733 | 55212 | 76623 | 3 |
| 5 | 31606 | 40182 | 3 | 49017 | 62816 | 92547 | 3 |
| 6 | 35996 | 46218 | 3 | 59787 | 73312 | 108669 | 2 |
| 8 | 47062 | 57686 | 3 | 70259 | 95163 | 140542 | 2 |
| 10 | 52017 | 68637 | 3 | 84901 | 114704 | 172123 | 2 |
| 12 | 60776 | 80756 | 3 | 99359 | 134600 | 203450 | 2 |
| 14 | - | - | - | - | 153634 | - | 1 |
| 16 | 76704 | 103047 | 2 | 128888 | 175971 | 267746 | 1 |
| 20 | 93426 | 126424 | 2 | 157343 | 216519 | 329970 | 1 |
| 24 | 109206 | 148610 | 2 | 185553 | 255680 | 391877 | 1 |

RR Kabel makes Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual Pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Individual Pair and Overall Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

| Size in Sq.mm / Rate Per 100 Meter (in INR) | | | | | | | |
|---|--------|--------|----------|--------|--------|--------|----------|
| Number of Pair | 0.50 | 0.75 | MOQ (KM) | 1.00 | 1.50 | 2.50 | MOQ (KM) |
| 2 | 22955 | 26830 | 5 | 30824 | 36977 | 49270 | 2 |
| 3 | 28678 | 33161 | 5 | 38606 | 48420 | 62734 | 2 |
| 4 | 34336 | 41297 | 3 | 48739 | 61012 | 80383 | 2 |
| 5 | 41617 | 51114 | 3 | 59338 | 70159 | 99114 | 1 |
| 6 | 48343 | 56276 | 2 | 66151 | 82198 | 116646 | 1 |
| 8 | 58234 | 71720 | 2 | 85557 | 106006 | 151414 | 1 |
| 10 | 70276 | 86956 | 1 | 104102 | 129584 | 185911 | 1 |
| 12 | 82198 | 102074 | 1 | 122506 | 153002 | 220217 | 1 |
| 16 | 106282 | 132777 | 1 | 158476 | 200868 | 290558 | 1 |
| 20 | 129816 | 162700 | 1 | 196524 | 247472 | 358994 | 1 |
| 24 | 153207 | 192501 | 1 | 232903 | 293912 | 427224 | 1 |
| 25 | - | - | - | 241980 | - | - | 1 |

Note: The MOQ is given above, please contact HO for Technical Data Sheet.

TERMS & CONDITIONS:

GST : The above prices are exclusive of GST.

Packing : Order should be in Standard packing.

Freight : Value upto Rs. 2,00,000/- on 'TO-PAY' basis & above on 'PAID' basis

Note : This is Revised Price List, hence all previous Price List & Discount will not be considered.

**As per the international practice which is also adopted by BIS, for all cables with ISI mark the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, it may vary within the prescribed limit of IS:8130, with related classes and tables.

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.



WORLD OF EXCELLENCE



As a USD 1.25+ billion conglomerate, we are one of the largest, diversified & most prominent brands in the Indian electrical industry, with a noteworthy presence in over 90+ countries across the world. We offer a multi faceted range of quality products through our 10 successfully operating companies, 43 marketing offices and 15 manufacturing facilities.

At RR Global, we continue to innovate to ensure only the finest products reach our customers.



Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.

T: +91 - 22 - 2494 9009 / 2492 4144 • **F:** +91 - 22 - 2491 2586 • **E:** mumbai.rrkabel@rrglobal.com

Alembic Business Park (W), Ground Floor, Bhailal Amin Marg, Gorwa, Vadodara - 390 003

T : +91-265-6830 800 • **E:** vadodara.rrkabel@rrglobal.com

R R KABEL LIMITED

Regd. Office : Ram Ratna House, Utopia City, P. B. Marg, Worli, Mumbai - 400 013.

Ahmedabad : 079-4900 0100, **Bengaluru :** 080-4125 0079 / 4090 2221, **Bhubaneswar :** 09776 060 012,

Chennai : 044-2829 2329 / 2429, **Coimbatore :** 09025 168 457, **Ernakulam :** 0484-2378 783,

Guwahati : 07227 004 919, **Indore :** 0731-3515 577, **Jaipur :** 0141-2741 417, **Jalandhar :** 0181-2910 637,

Kolkata : 033-6607 1233, **Lucknow :** 0522-3516 188 / 89, **Madurai :** 0452-4370 340,

New Delhi : 0124-6549 100, **Pune :** 08956 811 100, **Raipur :** 0771-2971 518, **Secunderabad :** 040-27804 098,

Silvassa : 0260-2641 332 / 333, **Surat :** 09376 507 543, **Trichy :** 08939 830 338.

www.rrkabel.com • www.rrglobal.com

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

RoHS = Restriction of Hazardous Substances | **CE** = Conformite Europeenne

ISI = Indian Standard Institution