

List of Products Covered in Our PCC LP

Aluminium Armoured / Unarmoured Cables

Copper Armoured / Unarmoured Cables

HT Cables

1.9 KV / 3.3 KV Cables for Solar

Instrumentation Cables

Rubber Cables

JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables

RS 485 Cables

Fire Survival Cables

FS Aluminium Cables

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		205	229		255
4		233	250		291
6		283	309		369
10		358	399		507
16	230	407	429		542
25	303	435	571	663	710
35	367	542	726	806	919
50	452	702	944	1092	1228
70	578	940	1294	1472	1668
95	693	1161	1594	1846	2080
120	804	1386	2000	2312	2612
150	958	1704	2455	2740	3212
185	1177	2048	3039	3469	3951
240	1454	2715	3881	4357	5102
300	1790	3328	4796	5360	6289
400	2261	4322	6130	6847	7850
500	2817	5835	8218	9678	10852
630	3475	7178	10447	11859	14246
800	4272				
1000	5254				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

FRLS Loading Factor			LSZH	
Cable Size (Sq.mm)	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		131	163		196
6		183	216		263
10		263	295		346
16	128	268	332		440
25	185	346	487	617	649
35	239	454	644	698	774
50	306	570	793	945	1035
70	422	820	1143	1291	1486
95	543	973	1390	1651	1771
120	677	1213	1869	2123	2259
150	837	1508	2199	2483	2796
185	1036	1798	2771	3177	3462
240	1315	2352	3577	3888	4523
300	1625	2875	4385	5039	5508
400	2092	3587	5471	6295	7040
500	2629	4576	7743	8687	9819
630	3257	5825	9714	11525	13140
800	4065				
1000	5125				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%	
b) Extruded PVC Innersheath Up 50	7.5%	
Extruded PVC Innersheath 70 & Above	4%	
c) HR PVC Insulation	17.5%	
d) HR PVC Inner Sheath	7.5%	
e) HR PVC Outer Sheath	7.5%	
f) Oxygen Index (FR)	4%	
g) PVC Insulated Cables	15%	

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
Power (Al.)				
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
Power Single Core (Al.)				
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	12%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XW _a Y / 2XF _a Y	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		495	663	850	1246	1570	1730
6		697	957	1251	1812	2214	2540
10		1108	1557	2033	2756		
16	946	1643	2277	3007	3953		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	252	356		14	1169	1837
3	321	460		16	1307	2087
4	396	594		19	1550	2457
5	482	729		24	1939	3076
6	573	858		27	2156	3450
7	631	968		30	2405	4149
8	807	1181		37	3120	4847
10	919	1360		44	3644	5660
12	1021	1580		61	5364	8206

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH			
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		Armoured				
2 to 4 Core	7.5%	9%	22.5%	22.5%		
5 to 10 Core	7.5%	6%	22.5%	22.5%		
12 & Above	7.5%	6%	18%	18%		

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance

only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market

convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core		3 Core	4 Core	
	2XY	2XY		2XY	2XY	
4		422		601	743	
6		616		887	1092	
10		1068		1504	1792	
16	791	1505		2185	2805	

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	197	298	14	968	1749
3	278	416	16	1159	2004
4	356	561	19	1387	2371
5	435	702	24	1757	2993
6	523	833	27	1940	3324
7	592	949	30	2303	3941
8	721	1076	37	2983	4726
10	860	1233	44	3489	5634
12	919	1509	61	5105	7754

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%	
B) Stranding (Upto 6 SQ.MM)	4%	
C) Extruded Innersheath	4%	
D OXYGEN INDEX (FR)	4%	
E) HR PVC Insulation	17.5%	
HR PVC I/S & O/S	7.5% Each	
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%	
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%	
G) PVC Insulated Cables	15%	

FRLS Loading Factor- Control Cable			LSZH		
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%	
5 - 10	7.5%	6%	22.5%	22.5%	
12 & Above	7.5%	6%	18%	18%	

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1431	2761	3769	4517	4968	7208
35	1944	3783	5308	6063	7048	9759
50	2627	4941	7175	8445	9563	13364
70	3690	7340	10477	12128	13804	21023
95	4904		14527	16635	19175	
120	6171		17813	21878	23892	
150	7676		22654	26466	30348	
185	9438		28796	33692	38464	
240	12125		37405	43488	49619	
300	15118		47144	54521	63095	
400	19762		60552	68909	84351	
500	24983					
630	31476					
800	39945					
1000	49825					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1299	2564	3564	4246	4667	
35	1797	3552	4966	5717	6687	
50	2460	4870	6751	8085	8939	
70	3503	6945	9944	11664	13208	
95	4776		14227	16558	18522	
120	6020		16655	21174	23714	
150	7523		22302	25760	29642	
185	9233		27524	32182	36699	
240	11927					
300	14878					
400	19549					
500	24702					
630	31053					
800	39521					
1000	49403					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoion	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1774				
50		2120				
70	2384	2583				
95	2691	2930	3961	4042	5355	
120	3258	3538	4451	4541	6037	
150	3825	4144	5104	5208	6489	7021
185	4387	4725	5761	5879	7244	7809
240	5348	5725	6802	6940	8556	9057
300	6393	6771	7974	8138	9659	10631
400	8108	8473	9673	9869	11708	12310

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	1961	2056	2154	2262	2439	2567	2496	2628	3211	3384	3677	3874
300	2246	2370	2469	2608	2778	2926	2842	2994	3796	3999	4085	4304
400	2731	2877	2962	3119	3299	3469	3372	3546	4356	4575	4609	4848
500	3484	3670	3611	3796	4144	4359	4144	4359	5132	5404	5348	5636
630	4209	4434	4323	4549	4897	5147	4897	5147	5968	6279	6214	6536
800	5231	5501	5304	5735	5866	6175	5866	6175	7063	7431	7370	7749
1000	6188	6513	6795	7158	7270	7646	7270	7646	8641	9059	9288	9775

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 240	1535
1 Core x 300	1850
1 Core x 400	2331
1 Core x 630	3626

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 25	830
3 Core x 35	941
3 Core x 50	1196
3 Core x 70	1456
3 Core x 95	1709
3 Core x 120	2237
3 Core x 150	2764
3 Core x 185	3255
3 Core x 240	4111
3 Core x 300	5036
3 Core x 400	6288

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAP INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	147	0.75	171	1	190	1.5	227	2.5	311
CORE	3	0.5	175	0.75	212	1	239	1.5	296	2.5	411
CORE	4	0.5	197	0.75	236	1	278	1.5	346	2.5	498
CORE	5	0.5	219	0.75	274	1	322	1.5	411	2.5	597
CORE	6	0.5	249	0.75	311	1	373	1.5	477	2.5	719
CORE	7	0.5	269	0.75	343	1	415	1.5	540	2.5	809
CORE	8	0.5	301	0.75	384	1	463	1.5	609	2.5	910
CORE	10	0.5	349	0.75	457	1	561	1.5	740	2.5	1127
CORE	12	0.5	392	0.75	519	1	634	1.5	852	2.5	1271
CORE	14	0.5	451	0.75	580	1	727	1.5	1002	2.5	1503
CORE	16	0.5	496	0.75	654	1	814	1.5	1109	2.5	1694
CORE	19	0.5	557	0.75	739	1	938	1.5	1268	2.5	1990
CORE	24	0.5	674	0.75	930	1	1139	1.5	1569	2.5	2498
PAIR	1	0.5	147	0.75	171	1	190	1.5	227	2.5	311
PAIR	2	0.5	214	0.75	257	1	296	1.5	368	2.5	527
PAIR	3	0.5	257	0.75	322	1	384	1.5	490	2.5	728
PAIR	4	0.5	307	0.75	391	1	472	1.5	616	2.5	925
PAIR	5	0.5	359	0.75	464	1	568	1.5	752	2.5	1144
PAIR	6	0.5	414	0.75	540	1	657	1.5	877	2.5	1334
PAIR	7	0.5	454	0.75	592	1	738	1.5	1013	2.5	1522
PAIR	8	0.5	509	0.75	676	1	834	1.5	1123	2.5	1723
PAIR	10	0.5	609	0.75	803	1	1007	1.5	1370	2.5	2102
PAIR	12	0.5	691	0.75	938	1	1185	1.5	1604	2.5	2505
PAIR	14	0.5	759	0.75	1052	1	1329	1.5	1853	2.5	2854
PAIR	16	0.5	866	0.75	1159	1	1502	1.5	2070	2.5	3240
PAIR	19	0.5	985	0.75	1371	1	1749	1.5	2420	2.5	3798
PAIR	24	0.5	1230	0.75	1722	1	2178	1.5	3041	2.5	4774
TRIAD	1	0.5	178	0.75	214	1	241	1.5	300	2.5	414
TRIAD	2	0.5	296	0.75	367	1	407	1.5	525	2.5	759
TRIAD	3	0.5	367	0.75	462	1	527	1.5	692	2.5	1023
TRIAD	4	0.5	441	0.75	567	1	659	1.5	869	2.5	1291
TRIAD	5	0.5	510	0.75	678	1	789	1.5	1065	2.5	1585
TRIAD	6	0.5	589	0.75	784	1	926	1.5	1229	2.5	1862
TRIAD	7	0.5	651	0.75	869	1	1033	1.5	1385	2.5	2122
TRIAD	8	0.5	733	0.75	955	1	1156	1.5	1570	2.5	2420
TRIAD	10	0.5	868	0.75	1185	1	1406	1.5	1934	2.5	2984
TRIAD	12	0.5	988	0.75	1361	1	1647	1.5	2258	2.5	3531
TRIAD	14	0.5	1123	0.75	1555	1	1883	1.5	2596	2.5	4066
TRIAD	16	0.5	1245	0.75	1733	1	2117	1.5	2941	2.5	4610
TRIAD	19	0.5	1436	0.75	2014	1	2465	1.5	3435	2.5	5406
TRIAD	24	0.5	1778	0.75	2521	1	3080	1.5	4326	2.5	6802
QUAD	1	0.5	204	0.75	249	1	287	1.5	357	2.5	511

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	292	0.75	328	1	371	1.5	452	2.5	625
PAIR	3	0.5	374	0.75	418	1	492	1.5	604	2.5	851
PAIR	4	0.5	449	0.75	514	1	598	1.5	757	2.5	1049
PAIR	5	0.5	529	0.75	608	1	721	1.5	887	2.5	1280
PAIR	6	0.5	584	0.75	706	1	810	1.5	1040	2.5	1491
PAIR	7	0.5	668	0.75	781	1	931	1.5	1176	2.5	1696
PAIR	8	0.5	759	0.75	863	1	1042	1.5	1333	2.5	1934
PAIR	10	0.5	895	0.75	1054	1	1269	1.5	1630	2.5	2373
PAIR	12	0.5	1000	0.75	1226	1	1465	1.5	1922	2.5	2715
PAIR	14	0.5	1158	0.75	1379	1	1682	1.5	2172	2.5	3212
PAIR	16	0.5	1304	0.75	1551	1	1886	1.5	2449	2.5	3634
PAIR	19	0.5	1489	0.75	1785	1	2181	1.5	2860	2.5	4249
PAIR	24	0.5	1852	0.75	2242	1	2741	1.5	3608	2.5	5345
TRIAD	2	0.5	361	0.75	415	1	470	1.5	584	2.5	807
TRIAD	3	0.5	449	0.75	529	1	613	1.5	777	2.5	1100
TRIAD	4	0.5	548	0.75	657	1	761	1.5	955	2.5	1397
TRIAD	5	0.5	649	0.75	784	1	921	1.5	1175	2.5	1732
TRIAD	6	0.5	750	0.75	895	1	1057	1.5	1376	2.5	2033
TRIAD	7	0.5	829	0.75	999	1	1186	1.5	1558	2.5	2311
TRIAD	8	0.5	927	0.75	1149	1	1348	1.5	1778	2.5	2636
TRIAD	10	0.5	1115	0.75	1389	1	1650	1.5	2182	2.5	3276
TRIAD	12	0.5	1291	0.75	1611	1	1927	1.5	2549	2.5	3840
TRIAD	14	0.5	1451	0.75	1832	1	2213	1.5	2942	2.5	4425
TRIAD	16	0.5	1633	0.75	2066	1	2485	1.5	3327	2.5	5021
TRIAD	19	0.5	1892	0.75	2401	1	2916	1.5	3912	2.5	5882
TRIAD	24	0.5	2373	0.75	3021	1	3675	1.5	4888	2.5	7446

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						658	955	1324	1883
2 Core	174	267	374	562	950	1455	2196	2980	4242
3 Core	231	372	530	796	1353	2068	3088	4225	6018
4 Core	301	483	694	1055	1780	2708	4049	5558	7977
5 Core	365	630	932						
6 Core	439	688							
7 Core	480	773							
8 Core	556	943							
10 Core	735	1164							
12 Core	881	1373							
14 Core	1002	1587							
16 Core	1161	1806							
19 Core	1353	2112							
24 Core	1726	2688							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	2646	3471	4401	5477	6675	8818	11043	14500	
3 Core	8480	11119	14094	17541	21377	28123	35272	46144	
4 Core	11117	14570	18589	23139	28216	37112	46495	61019	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	127	199				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	184	295	430	925	1963	3605

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	147	280	445			

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	178
	22 AWG	0.32	195
	20 AWG	0.50	217
	18 AWG	0.80	256
	17 AWG	1.00	275
2 Pair	24 AWG	0.205	256
	22 AWG	0.32	287
	20 AWG	0.50	325
	18 AWG	0.80	398
	17 AWG	1.00	434

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	109
	22 AWG	0.32	123
	20 AWG	0.50	140
	18 AWG	0.80	174
	17 AWG	1.00	189
2 Pair	24 AWG	0.205	162
	22 AWG	0.32	195
	20 AWG	0.50	225
	18 AWG	0.80	290
	17 AWG	1.00	327

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	195
	22 AWG	0.32	214
	20 AWG	0.50	239
	18 AWG	0.80	281
	17 AWG	1.00	303
2 Pair	24 AWG	0.205	281
	22 AWG	0.32	313
	20 AWG	0.50	356
	18 AWG	0.80	436
	17 AWG	1.00	479

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	119
	22 AWG	0.32	135
	20 AWG	0.50	154
	18 AWG	0.80	190
	17 AWG	1.00	211
2 Pair	24 AWG	0.205	181
	22 AWG	0.32	214
	20 AWG	0.50	248
	18 AWG	0.80	318
	17 AWG	1.00	358

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	396	492		600
2.5	492	631		778
4	579	759		950
6	752	1004		1270
10	1062	1452		1855
16	1407	1965		2584
25	2007	2890	3480	3797
35	2670	3871	4474	5109
50	3516	5141	6030	6808
70	4889	7182	8402	9513
95	6425	9461	11049	12540
120	7995	11822	14086	15697
150	9790	14497	16751	19236
185	12095	17927	20988	23783
240	15379	22841	26694	30332
300	19051	28301	33030	37620
400	24799	36893	42757	49041

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	441	542		657
2.5	542	683		836
4	632	813		1010
6	804	1063		1335
10	1123	1516		1928
16	1467	2027		2668
25	2082	2972	3572	3893
35	2751	3964	4575	5217
50	3607	5242	6141	6935
70	5000	7312	8544	9664
95	6555	9600	11205	12708
120	8131	11976	14272	15899
150	9952	14686	16961	19472
185	12276	18153	21238	24059
240	15596	23111	26996	30664
300	19309	28617	33382	38019
400	25123	37296	43210	49537

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	459	568		687
2.5	563	710		870
4	651	839		1048
6	825	1096		1379
10	1148	1554		1980
16	1496	2074		2726
25	2129	3045	3658	3987
35	2805	4042	4670	5324
50	3677	5348	6267	7073
70	5091	7449	8707	9847
95	6652	9749	11389	12905
120	8251	12158	14498	16142
150	10107	14921	17240	19787
185	12479	18453	21588	24457
240	15836	23474	27422	31148
300	19592	29042	33887	38588
400	25477	37825	43845	50247

Page 17 of 18

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	823	1064
25	1109	1410
35	1342	1732
50	1660	2150
70	2267	2952
95	2833	3688
120	3386	4437
150	4029	5278
185	4883	6377
240	6076	7947
300	7315	9599
400	9101	11922