



KEI INDUSTRIES LTD.

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
spa.mumbai@kei-ind.com



PRICE LIST : 1st DEC 2025

LP NO. KEI/LDC/LP/25-26/07 DT.01.12.2025

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

(Rate in Rs. Per 100 Mtrs)

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.50	16/0.20	3870	5350	6890	8650	10540	11880	17510	20740	24000	27170	31760	40520
0.75	24/0.20	5360	7510	9780	12250	14890	16880	24780	29370	34050	38640	45310	57750
1.00	32/0.20	6450	9150	11980	15250	18490	21050	30810	36560	42430	48210	56630	72140
1.50	30/0.25	9040	12950	16980	21770	26170	29580	42370	50820	59160	67330	79520	100110
2.50	50/0.25	14780	21250	27920	35320	42470	48160	68980	82730	96390	109820	129900	163730
4.00	56/0.3	23800	34390	45350	57640	69290	78780	112710	135180	157480	179570	212900	268460
6.00	84/0.3	34870	50720	67130	85450								
10.00	80/0.4	59760	87200	115530	144980								
16.00	126/0.4	92510	135500	179660									
25.00	196/0.4		206280	274460									
35.00	276/0.4		288670	384140									
50.00	396/0.4		413060	549810									
70.00	354/0.5		583770	777210									
95.00	484/0.5			1027220									

KEI FLEXIBLE PVC INSULATED MULTICORE FRLS PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.50	16/0.20	4410	5920	7550	9500	11640	12660	18230	21870	25360	28610	33420	42150
0.75	24/0.20	5990	8190	10570	13260	16190	17800	25820	30680	35640	40340	47300	60060
1.00	32/0.20	7070	9890	12850	16370	19930	22060	31970	37990	44160	50070	58830	74840
1.50	30/0.25	9780	13870	18070	23230	27960	31160	44690	53590	62330	70820	83420	104880
2.50	50/0.25	15910	22680	29630	37380	44990	50380	72230	86620	100850	114750	135480	170590
4.00	56/0.3	25600	36440	47810	60710	73050	82090	117540	140940	164090	186920	221440	279000
6.00	84/0.3	37270	53470	70560	89840								
10.00	80/0.4	63530	91590	121000	152020								
16.00	126/0.4	97850	141820	187580									
25.00	196/0.4		214690	285360									
35.00	276/0.4		300040	398920									
50.00	396/0.4		428910	570460									
70.00	354/0.5		605530	805630									
95.00	484/0.5			1065550									

KEI FLEXIBLE PVC INSULATED MULTICORE ZHFR/HFFR THERMOPLASTIC COMPOUND SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V GENERALLY CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.50	16/0.20	4450	5980	7630	9600	11760	12790	18410	22090	25610	28900	33750	42570
0.75	24/0.20	6050	8270	10680	13390	16350	17980	26080	30990	36000	40740	47770	60660
1.00	32/0.20	7140	9990	12980	16530	20130	22280	32290	38370	44600	50570	59420	75590
1.50	30/0.25	9880	14010	18250	23460	28240	31470	45140	54130	62950	71530	84250	105930
2.50	50/0.25	16070	22910	29930	37750	45440	50880	72950	87490	101860	115900	136830	172300
4.00	56/0.3	25860	36800	48290	61320	73780	82910	118720	142350	165730	188790	223650	281790
6.00	84/0.3	37640	54000	71270	90740	Note : • Multicore Flexible cables available in coil/drum packing. • GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy. • Please refer to our Marketing Department for Wires & Cables, not covered above. • This Price List is subject to change without prior notice.							
10.00	80/0.4	64170	92510	122210	153540								
16.00	126/0.4	98830	143240	189460									
25.00	196/0.4		216840	288210									
35.00	276/0.4		303040	402910									
50.00	396/0.4		433200	576160									
70.00	354/0.5		611590	813690									
95.00	484/0.5			1076210									