

RR KABEL LIMITED													
RRKL/CU-ARM-UAR/LP/01/26						w.e.f. 16th January, 2026							
PRICE LIST													
POWER CABLES (COPPER ARMoured / UNARMoured)													
RR KABEL make Power/Control Cables, Solid Copper Conductor upto 6.0 Sq.mm balance Stranded, XLPE Insulated, cores laid up, PVC tape inner sheathed for Multicore Cables, Unarmoured / Armour (1. Single core cables - Aluminium wire upto 70.0 sq.mm balance Aluminum strip, 2. Glavanised wire for cables upto 10Cx1.5 sq.mm, 8Cx2.5 sq.mm, 2Cx10.0 sq.mm, 3Cx10.0 Sq.mm, 4Cx6.0 Sq.mm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/ 1100 V grade as per IS 7098 (Part 1) 1988. (HSN CODE : 8544)													
Rate Per Meter (INR)													
(UNARMoured CABLES) (2XY)						(ARMoured CABLES) (2XWY / 2XFY)							
No. of Cores	1.5	2.5	No. of Cores	1.5	2.5	No. of Cores	1.5	2.5	No. of Cores	1.5	2.5		
2	244	369	14	1198	2165	2	312	441	14	1447	2274		
3	344	515	16	1434	2481	3	397	570	16	1617	2583		
4	441	694	19	1716	2934	4	491	735	19	1918	3040		
5	538	869	24	2175	3704	5	596	902	24	2399	3807		
6	647	1031	27	2401	4114	6	710	1062	27	2669	4269		
7	733	1175	30	2850	4877	7	781	1198	30	2977	5135		
8	892	1332	37	3692	5849	8	999	1462	37	3861	5998		
10	1065	1526	44	4318	6972	10	1137	1683	44	4510	7005		
12	1137	1868	61	6317	9595	12	1264	1956	61	6639	10155		
Size (Sq.mm)	(UNARMoured CABLES) (2XY)					(ARMoured CABLES) (2XWY/2XFY) (2XWY / 2XFY)							
	1 Core	2 Core	3 Core	3.5 Core	4 Core	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core	6 Core	7 Core
4.0	-	534	761	-	941	-	627	839	-	1076	1577	1987	2189
6.0	-	780	1123	-	1383	-	882	1212	-	1583	2294	2802	3215
10.0	-	1352	1904	-	2268	-	1403	1971	-	2573	3489	-	-
16.0	1001	1904	2765	-	3549	1197	2078	2881	-	3804	5000	-	-
25.0	1572	3102	4312	5138	5647	1731	3341	4561	5466	6012	8722	-	-
35.0	2175	4298	6009	6918	8092	2352	4577	6423	7336	8528	11809	-	-
50.0	2977	5893	8169	9783	10816	3179	5979	8682	10219	11571	16170	-	-
70.0	4238	8404	12032	14113	15982	4465	8881	12678	14675	16702	25438	-	-
95.0	5779	11487	17215	20035	22411	5933	12272	17578	20129	23202	-	-	-
120.0	7284	14516	20153	25620	28694	7467	14633	21553	26473	28909	-	-	-
150.0	9103	18105	26985	31170	35867	9288	18322	27411	32024	36721	-	-	-
185.0	11172	21870	33304	38940	44406	11420	22679	34844	40767	46541	-	-	-
240.0	14432	28002	43526	50847	58840	14672	29217	45261	52621	60039	-	-	-
300.0	18003	34891	53983	62690	72663	18293	37005	57044	65970	76346	-	-	-
400.0	23654	46569	67294	76648	95598	23912	50340	73268	83380	102065	-	-	-
500.0	29889	-	-	-	-	30229	-	-	-	-	-	-	-
630.0	37574	-	-	-	-	38086	-	-	-	-	-	-	-
800.0	47820	-	-	-	-	48334	-	-	-	-	-	-	-
1000.0	59777	-	-	-	-	60289	-	-	-	-	-	-	-
Additional to be charged for Special Construction													
A) Tinning	3%		G) HR PVC Insulation		10%		As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the Price List are only for guidelines and as per market convention, it may vary within the prescribed limit of IS:8130-1994, with related classes and tables.						
B) Stranding (upto 6.0 Sq.mm)	4%		H) HR PVC Inner Sheath		7.5%								
C) Extruded Inner Sheath	4.0%		I) HR PVC Outer Sheath		7.5%								
D) Round Wire Armouring:			J) FR-LSH Outer Sheath (Power Cables)										
1. 1C x 95.0 Sq.mm & above	9.0%		Upto 6.0 Sq.mm		11.5%								
2. 12C x 1.5 Sq.mm & above	18%		10.0 Sq.mm & above		6%								
3. 9C x 2.5 Sq.mm & above	18%		K) FR-LSH / LSZH Loading - Control Cables (Inner / Outer Sheath)										
4. 4C x 10.0 Sq.mm & above	18%												
5. 2C x 16.0 & above	18%		Cores	FR-LSH		LSZH		* MOQ will be applicable for all Special Items					
6. 3C x 16.0 & above	18%			Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath						
E) Oxygen Index (FR)	4.0%		2C to 4C		7.5%		9%		22.5%		22.5%		* The above material will be supplied from our Waghodia Unit.
F) PVC Insulation (as per IS 1554)	7.5%		5C to 10C		7.5%		6%		18.0%		18.0%		
Terms & Conditions:													
> The above rates are exclusive of GST & any other statutory levies which shall be charged extra.													
> Freight will be Extra as applicable													
Note: This is revised Price List, hence our all previous Price Lists, Discount Policies are hereby ceased to exist.													
THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE													

RR KABEL LIMITED

RRKL/AL-ARM-UAR/LP/01/26

w.e.f. 16th January, 2026

PRICE LIST
POWER CABLES (AL. ARMoured / UNARMoured)

RR KABEL make Power Cables, Solid Aluminum conductor upto 10.0 sq.mm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape inner sheathed for Multicore Cables, Unarmoured / Armour (1. Single core Cables - Aluminium wire upto 70.0 sq.mm balance Aluminum strip, 2. Galvanised wire for cables upto 2Cx10.0 sq.mm, 3Cx10.0 sq.mm, 4Cx6.0 sq.mm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/ 1100 V grade as per IS 7098 (Part 1) 1988. (HSN Code : 8544)

Size (in Sq.mm)	CORES / RATE PER METER (INR)									
	(UNARMoured CABLES) (A2XY)					(ARMoured CABLES) (A2XW _a Y/ A2XF _a Y) (A2XWY / A2XFY)				
	1C	2C	3C	3.5C	4C	1C	2C	3C	3.5C	4C
4.0	-	150	187	-	224	-	260	280	-	326
6.0	-	209	248	-	301	-	316	345	-	413
10.0	-	301	338	-	396	-	400	446	-	567
16.0	146	307	380	-	504	257	455	479	-	606
25.0	211	396	557	706	743	339	486	639	742	793
35.0	274	519	737	799	886	411	606	812	901	1028
50.0	350	652	908	1081	1184	505	785	1056	1221	1373
70.0	483	938	1308	1477	1700	646	1051	1447	1646	1865
95.0	622	1113	1591	1889	2026	775	1298	1782	2064	2325
120.0	782	1401	2158	2452	2609	907	1564	2258	2610	2949
150.0	967	1741	2540	2868	3230	1081	1923	2771	3093	3626
185.0	1197	2077	3201	3670	3999	1329	2311	3430	3915	4460
240.0	1519	2717	4132	4490	5224	1642	3065	4381	4918	5759
300.0	1877	3321	5064	5820	6361	2021	3756	5414	6050	7098
400.0	2417	4143	6320	7271	8131	2552	4878	6920	7728	8861
500.0	3036	5286	8943	10033	11341	3180	6587	9276	10924	12250
630.0	3762	6728	11220	13311	15177	3923	8102	11792	13386	16080
800.0	4695	-	-	-	-	4822	-	-	-	-
1000.0	5919	-	-	-	-	5931	-	-	-	-

Additional to be charged for Special Construction

A) Stranding (upto 10.0 Sq.mm)	10%	H) FR-LSH / LSZH Loading - (Inner / Outer Sheath) :					
B) Round Wire Armouring		Size	FR-LSH		LSZH		
			Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	1. 1C x 95.0 & above	30%	Upto 1C x 16.0	NA	15%	NA	37.50%
	2. 2C x 16.0 & above	30%	1C x 25.0 to 1C x 50.0	NA	15%	NA	30%
	3. 3C x 16.0 & above	30%	1C x 70.0 & above	NA	11.50%	NA	26.0%
	4. 3.5C x 25.0 & above	30%	Multicore upto 16.0	15%	11.5%	22.5%	30%
5. 4C x 10.0 & above	30%						
C) Oxygen Index (FR)	4.0%	Multicore 25.0 to 50.0	11.5%	11.5%	18.0%	22.5%	
D) PVC Insulation (as per IS 1554)	12%	Multicore 70.0 & above	7.5%	7.5%	22.5%	18%	
E) HR PVC Insulation	15%	I) Extruded PVC Inner Sheath :			* MOQ will be applicable for all Special Items		
F) HR PVC Inner Sheath	7.50%	1. Upto 50.0 Sq.mm.	5%				
G) HR PVC Outer Sheath	7.50%	2. 70.0 Sq.mm. & above	2.5%				

Terms & Conditions:

> The above rates are exclusive of GST & any other statutory levies which shall be charged extra.

> Freight will be Extra as applicable

Note: This is revised Price List, hence our all previous Price Lists, Discount Policies are hereby ceased to exist.

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE