



Electrical & Automation

for  
*Homes*



Retail Products Price List  
Maximum Retail Prices  
Effective from 01-06-2026

©2026. ALL RIGHTS RESERVED

Trippler® | enConnect® | englaze® | entice | enCurve | enGem

## HIGHLIGHTS

- marked, marked
- Conforms to IS/IEC 60898 - 6 kA
- Higher life with use of heavy duty contacts
- Innovatively designed breathing channels between poles ensure cooler operation
- Energy saving - watt loss approximately 50% lower than those prescribed by IEC standard
- Manufactured with high quality fire retardant material
- True contact indication for enhanced safety



## MINIATURE CIRCUIT BREAKERS (MCBs) - B CURVE



Description	Single Pole			
	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
6A B Curve	1	BA10060B	246	1/12
10A B Curve	1	BA10100B	246	1/12
16A B Curve	1	BA10160B	246	1/12
20A B Curve	1	BA10200B	246	1/12
25A B Curve	1	BA10250B	246	1/12
32A B Curve	1	BA10320B	246	1/12
40A B Curve	1	BA10400B	583	1/12

## MINIATURE CIRCUIT BREAKERS (MCBs) - C CURVE

Description	Single Pole				Double Pole				Three Pole				Four Pole			
	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
6A C Curve	1	BA10060C	246	1/12	2	BA20060C	955	1/6	3	BA30060C	1570	1/4	4	BA40060C	2125	1/3
10A C Curve	1	BA10100C	246	1/12	2	BA20100C	955	1/6	3	BA30100C	1570	1/4	4	BA40100C	2125	1/3
16A C Curve	1	BA10160C	246	1/12	2	BA20160C	955	1/6	3	BA30160C	1570	1/4	4	BA40160C	2125	1/3
20A C Curve	1	BA10200C	246	1/12	2	BA20200C	955	1/6	3	BA30200C	1570	1/4	4	BA40200C	2125	1/3
25A C Curve	1	BA10250C	246	1/12	2	BA20250C	955	1/6	3	BA30250C	1570	1/4	4	BA40250C	2125	1/3
32A C Curve	1	BA10320C	246	1/12	2	BA20320C	955	1/6	3	BA30320C	1570	1/4	4	BA40320C	2125	1/3
40A C Curve	1	BA10400C	583	1/12	2	BA20400C	1430	1/6	3	BA30400C	2240	1/4	4	BA40400C	2755	1/3
63A C Curve	1	BA10630C	649	1/12	2	BA20630C	1590	1/6	3	BA30630C	2405	1/4	4	BA40630C	2930	1/3



\*Module Width: 1 Mod = 17.5 mm

## HIGHLIGHTS

- marked, marked
- Conforms to IS 12640 - 1, IEC 61008-1
- Available in DP & FP versions from 25A to 63A ratings with 30mA, 100mA & 300mA sensitivity
- Operates on Core Balance Current Transformer (CBCT) principle
- Finger proof IP20 terminals



## RESIDUAL CURRENT CIRCUIT BREAKERS (RCCBs/ELCBs)

Description	Double Pole				Four Pole			
	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
25A 30mA	2	BC202503	2995	1	4	BC402503	4100	1
25A 100mA	2	BC202510	3275	1	4	BC402510	4175	1
25A 300mA	2	BC202530	3275	1	4	BC402530	4175	1
<b>New</b> 32 A 30mA	2	BC203203	3395	1	4	BC403203	4165	1
<b>New</b> 32A 100mA	2	BC203210	3440	1	4	BC403210	4250	1
<b>New</b> 32A 300mA	2	BC203230	3440	1	4	BC403230	4250	1
40A 30mA	2	BC204003	3395	1	4	BC404003	4090	1
40A 100mA	2	BC204010	3440	1	4	BC404010	4250	1
40A 300mA	2	BC204030	3440	1	4	BC404030	4250	1
63A 30mA	2	BC206303	4340	1	4	BC406303	4595	1
63A 100mA	2	BC206310	4525	1	4	BC406310	4745	1
63A 300mA	2	BC206330	4525	1	4	BC406330	4745	1
<b>New</b> 100A 30mA	2	BC210003	7495	1	4	BC410003	8135	1
<b>New</b> 100A 100mA	2	BC210010	7590	1	4	BC410010	8430	1
<b>New</b> 100A 300mA	2	BC210030	7590	1	4	BC410030	8430	1



## HIGHLIGHTS

- marked
- Conforms to IEC 60947 - 3
- Higher life with use of heavy duty contacts
- Innovatively designed breathing channels between poles ensure cooler operation
- Manufactured with high quality fire retardant material
- True contact indication for enhanced safety



## ISOLATORS

Description	Double Pole				Three Pole				Four Pole			
	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
40A Isolator	2	BE204000	610	1/6	3	BE304000	1075	1/4	4	BE404000	1385	1/3
63A Isolator	2	BE206300	760	1/6	3	BE306300	1230	1/4	4	BE406300	1440	1/3
100A Isolator	2	BE210000	1055	1/6	3	BE310000	1455	1/4	4	BE410000	1735	1/3

\*Module Width: 1 Mod = 17.5 mm

## HIGHLIGHTS

- CE marked
- Conforms to IEC 60947-6, IEC 60947-3
- Wide Range of Current Ratings
  - Generator Side - 1.5A to 30A
  - Electricity Board Side - 30A
- No. of Poles 1P+N, for single phase applications
- Protection Degree - IP20
- Reliable microcontroller based design for sensing & control
- Lower power consumption
- RoHS compliant



## HIGHLIGHTS

- Settable overload current limit at DG side
- Separate power consumption monitoring for Mains & Genset
- Settable overvoltage & undervoltage protection
- Settable TPN or SPN mode at DG side
- Protection against single phasing

For 3 Phase ACCL programming video please scan the QR code or click here



## HIGHLIGHTS

- Conforms to IEC 60947-3
- Available with 3 positions (I-O-II) with centre off position
- Utilization category AC-22A



## AUTOMATIC CHANGEOVER WITH CURRENT LIMITER(ACCL)



	Description EB/DG	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
<b>New</b>	30A/1A	4	BCL01030001	2360	1
	30A/1.5A	4	BCL010301E5	2360	1
<b>New</b>	30A/2A	4	BCL01030002	2360	1
	30A/2.5A	4	BCL010302E5	2360	1
	30A/3A	4	BCL01030003	2360	1
	30A/4A	4	BCL01030004	2360	1
	30A/5A	4	BCL01030005	2360	1
	30A/6A	4	BCL01030006	2360	1
	30A/8A	4	BCL01030008	2360	1
	30A/10A	4	BCL01030010	2360	1
	30A/12A	4	BCL01030012	2360	1
	30A/15A	4	BCL01030015	2360	1
	30A/20A	4	BCL01030020	2360	1
	30A/30A <sup>#</sup>	4	BCL01030030	2360	1

<sup>#</sup>Non current limiting variant

## THREE PHASE AUTOMATIC CHANGEOVER WITH CURRENT LIMITER (3PH ACCL) **NEW**



Description (AC-1) EB/DG	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
32A / 32A	AUCL03032032	18415	1
40A / 32A	AUCL03040032	18975	1
40A / 40A	AUCL03040040	20540	1
50A / 50A	AUCL03050050	29275	1
63A / 50A	AUCL03063050	32300	1
63A / 63A	AUCL03063063	36590	1
80A / 80A	AUCL03080080	55765	1
125A / 125A	AUCL03125125	93870	1

## MODULAR CHANGEOVER SWITCHES

Double Pole					Four Pole				
Description	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)	Description	MW*	Cat No	MRP/Unit in ₹	Std. Pkg. (Nos.)
25A	2	AUC00202500	2270	1	40A	4	AUC00404000	5985	1
40A	2	AUC00204000	3475	1	63A	6	AUC00406300	6785	1
63A	3	AUC00206300	4040	1					

\*Module Width: 1 Mod = 17.5 mm

## HIGHLIGHTS

- marked, C marked
- Conforms to IS 12640-2, IEC 61009-1, EN 61009-1
- Short Circuit Breaking Capacity - 10kA
- Wide range of current ratings - 6A to 100A
- Suitable for Isolation
- Safety Shutter
- Line-load Reversibility
- True Position Indication
- Trip-free Mechanism
- Easy fault identification -
  1. Short Circuit fault Indication :  
Clear indication by amber coloured flag
  2. Earth Leakage Fault Indication :  
Clear indication by yellow coloured flag



## RESIDUAL CURRENT CIRCUIT BREAKER WITH OVER CURRENT PROTECTION (RCBOs)

**NEW**

### Double Pole

Description	100 mA				300 mA							
	MW*	Cat No (30 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No (100 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No (300 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)
6A 2P RCBO	2	AUF3C200603	6710	1	2	AUF3C200610	6850	1	2	AUF3C200630	6930	1
10A 2P RCBO	2	AUF3C201003	6710	1	2	AUF3C201010	6850	1	2	AUF3C201030	6930	1
16A 2P RCBO	2	AUF3C201603	6710	1	2	AUF3C201610	6850	1	2	AUF3C201630	6930	1
20A 2P RCBO	2	AUF3C202003	6710	1	2	AUF3C202010	6850	1	2	AUF3C202030	6930	1
25A 2P RCBO	2	AUF3C202503	6710	1	2	AUF3C202510	6850	1	2	AUF3C202530	6930	1
32A 2P RCBO	2	AUF3C203203	6710	1	2	AUF3C203210	6850	1	2	AUF3C203230	6930	1
40A 2P RCBO	2	AUF3C204003	6710	1	2	AUF3C204010	6850	1	2	AUF3C204030	6930	1
63A 2P RCBO	4	AUF3C206303	7970	1	4	AUF3C206310	8455	1	4	AUF3C206330	8520	1

## RESIDUAL CURRENT CIRCUIT BREAKER WITH OVER CURRENT PROTECTION (RCBOs)

**NEW**

### Four Pole

Description	100 mA				300 mA							
	MW*	Cat No (30 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No (100 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)	MW*	Cat No (300 mA)	MRP/Unit in ₹	Std. Pkg. (Nos.)
C16A 4P RCBO	7.5	AUF3C401603	7205	1	7.5	AUF3C401610	8020	1	7.5	AUF3C401630	8180	1
C20A 4P RCBO	7.5	AUF3C402003	7205	1	7.5	AUF3C402010	8020	1	7.5	AUF3C402030	8180	1
C25A 4P RCBO	7.5	AUF3C402503	7205	1	7.5	AUF3C402510	8020	1	7.5	AUF3C402530	8180	1
C32A 4P RCBO	7.5	AUF3C403203	7440	1	7.5	AUF3C403210	8025	1	7.5	AUF3C403230	8205	1
C40A 4P RCBO	7.5	AUF3C404003	7555	1	7.5	AUF3C404010	8025	1	7.5	AUF3C404030	8230	1
C63A 4P RCBO	7.5	AUF3C406303	9055	1	7.5	AUF3C406310	9225	1	7.5	AUF3C406330	9225	1
C80A 4P RCBO	12	AUF3C408003	35090	1	12	AUF3C408010	35875	1	12	AUF3C408030	35875	1
C100A 4P RCBO	12	AUF3C410003	37515	1	12	AUF3C410010	38410	1	12	AUF3C410030	38410	1



\*Module Width: 1 Mod = 17.5 mm

Tripbox NXT



Designed for safety.  
Styled for you.

Tripbox NXT



Over-The-Frame Design  
Delivers Higher Protection

Curved Door  
Adds a Stylish Touch

Uniform Gasketing  
Ensures Press Protection

DESIGNED FOR SAFETY

STYLED FOR YOU

## SPN DISTRIBUTION BOARDS

- Available in 4, 6, 8, 12 & 16 way
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bar, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- Choice of metal and glazed door
- With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoings



## SPN DISTRIBUTION BOARDS

**NEW**

Description	Modules		Double Door	MRP/Unit in ₹	Double Door - Glazed	MRP/Unit in ₹
	Incomer	Outgoing				
4-Way	2	2	DTSPN004DD	1960	DTSPN004GD	2580
6-Way	2	4	DTSPN006DD	2300	DTSPN006GD	2760
8-Way	2	6	DTSPN008DD	2445	DTSPN008GD	3015
12-Way	2	10	DTSPN012DD	2940	DTSPN012GD	3655
16-Way	2	14	DTSPN016DD	3680	DTSPN016GD	4520
18-Way	2	16	DTSPN018DD	3830	DTSPN018GD	4785

## TPN DISTRIBUTION BOARDS

- Available in 4, 6, 8 & 12 way
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- Choice of metal and glazed door
- With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoings



## TPN DISTRIBUTION BOARDS

**NEW**

Description	Modules		Double Door	MRP/Unit in ₹	Double Door - Glazed	MRP/Unit in ₹
	Incomer	Outgoing				
4-Way	8	4+4+4	DTPN004DD	4855	DTPN004GD	6335
6-Way	8	6+6+6	DTPN006DD	6055	DTPN006GD	7860
8-Way	8	8+8+8	DTPN008DD	7240	DTPN008GD	9400
12-Way	8	12+12+12	DTPN012DD	10770	DTPN012GD	14390

## HORIZONTAL PPI (PER PHASE ISOLATION) DBs

- Available in 4, 6, 8 & 12 way
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- With provision for FP MCB/Isolator/RCCB/RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoings



## HORIZONTAL PPI (PER PHASE ISOLATION) DBs

**NEW**

Description	Modules			Double Door	MRP/Unit in ₹
	Incomer	Sub-Incomer	Outgoing		
4-Way	8	2+2+2	4+4+4	DTHPI004DD	8025
6-Way	8	2+2+2	6+6+6	DTHPI006DD	9620
8-Way	8	2+2+2	8+8+8	DTHPI008DD	11470
12-Way	8	2+2+2	12+12+12	DTHPI012DD	15630

### Flexi/ROW DBs

- Available in 2 Row 28 Mod, 3 Row 42 Mod, 3 Row 56 Mod, 4 Row 64 Mod
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- Gives flexibility to customer to mount modular devices as per requirement



### FLEXI/ROW DBs

**NEW**

Description	Modules		IP 43 Metal Door	MRP/Unit in ₹
	Incomer	Outgoing		
2 Row 28 Module	8	4+4+4	DTROW228DD	6450
3 Row 42 Module	8	4+4+4	DTROW342DD	7735
4 Row 56 Module	8	4+4+4	DTROW456DD	8410
4 Row 64 Module	8	4+4+4	DTROW464DD	9785

### PHASE SEGREGATED DBs

- Available in 4, 6, 8 & 12 way
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- With provision for FP MCB/Isolator as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



### PHASE SEGREGATED DBs

**NEW**

Description	Modules			Double Door	MRP/Unit in ₹
	Incomer	Sub-Incomer	Outgoing		
4-Way	8	4+4+4	4+4+4	DTPSG004DD	12645
6-Way	8	4+4+4	6+6+6	DTPSG006DD	14275
8-Way	8	4+4+4	8+8+8	DTPSG008DD	15940
12-Way	8	4+4+4	12+12+12	DTPSG012DD	20115

### PHASE SELECTOR DBs

- Available in 4, 6, 8 & 12 way
- Provided with 63A Selector Switches
- Ready to use DBs, complete with colour - coded wire set, 100A insulated bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cable ties, Blanking plates and Circuit identification label
- With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



### PHASE SELECTOR DBs

**NEW**

Description	Modules		Double Door	MRP/Unit in ₹
	Incomer	Outgoing		
4-Way	8	4+4+4	DTPSR004DD	15070
6-Way	8	6+6+6	DTPSR006DD	15435
8-Way	8	8+8+8	DTPSR008DD	16365
12-Way	8	12+12+12	DTPSR012DD	18360

### VTPN DBs WITH MODULAR INCOMER

- Available in 4, 6, 8 & 12 way
- Ready to use DBs, complete with colour - coded wire set, Insulated vertical phase bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP/TP MCBs as outgoing



### VTPN DBs WITH MODULAR INCOMER

**NEW**

Description	Modules		Double Door	MRP/Unit in ₹
	Incomer	Outgoing		
4-Way	8	4+4+4	DTVTM004DD	11625
6-Way	8	6+6+6	DTVTM006DD	13365
8-Way	8	8+8+8	DTVTM008DD	15510
12-Way	8	12+12+12	DTVTM012DD	20520

## VTPN DBs WITH MCCB INCOMER

- Available in 4, 6, 8 & 12 way
- Ready to use DBs, complete with colour - coded wire set, Insulated vertical phase bus bars, Neutral bar/s with shroud/s, Earth bar/s, Cement Spill Protector, Cable ties, Blanking plates and Circuit identification label
- With provision for MCCB as incomer and SP/TP MCBs as outgoing
- Suitable for 3P/4P MCCB as incomer upto 125A - DY125U



## VTPN DBs WITH MCCB INCOMER **NEW**

Description	Modules		Double Door	MRP/Unit in ₹
	Incomer	Outgoing		
4-Way	MCCB	4+4+4	DTVTL004DD	13875
6-Way	MCCB	6+6+6	DTVTL006DD	16240
8-Way	MCCB	8+8+8	DTVTL008DD	17635
12-Way	MCCB	12+12+12	DTVTL012DD	22805

## DBS WITH PROVISION FOR TV / TELEPHONE SPLITTERS

- Distribution Boards equipped with provisions to mount TV / Telephone splitters
- Available in SPN & TPN Dbs
- Communication DB equipped with provisions to mount 2 ONT, Spike guard, Data switch, TV / Telephone splitters



## DBS WITH PROVISION FOR TV / TELEPHONE SPLITTERS **NEW**

DB Type	Description	Modules		IP 43 Metal Door	MRP/Unit in ₹
		Incomer	Outgoing		
SPN	6 way	2	4	DTSPN006DDTV	4490
	8 way	2	6	DTSPN008DDTV	4825
	12 way	2	10	DTSPN012DDTV	5940
	16 way	2	14	DTSPN016DDTV	6890
	18 way	2	16	DTSPN018DDTV	8155
TPN	4 way	8	4+4+4	DTTPN004DDTV	8825
	6 way	8	6+6+6	DTTPN006DDTV	10195
	8 way	8	8+8+8	DTTPN008DDTV	12155
Communication DB				DTCOM01DD	*

## EV CHARGING DB

- Engineered specifically Charging application-3.3kW
- Robust earth leakage, short circuit and overload protection with RCBO
- Factory fitted RCBO, switch and socket



## EV CHARGING DB **NEW**

Description	Modules	IP 43 Metal Door	MRP/Unit in ₹
2 way EVDB	2	DTEVC002LD	*
4 way EVDB	4	DTEVC004LD	*

\*For details, please contact nearest branch office

## ENCLOSURES

- Available in 2, 3, 4 & 6 way
- With provision to mount MCB/Isolator/RCCB/RCBO or other modular devices



Single Door

## PLUG & SOCKET DBs

- SPN 10A & 20A; TPN - 32A
- With provision to mount MCBs/RCCBs



Single Door

## METAL PLUG & SOCKET

- Designed to ensure safe functioning of electrical equipment and the user safety
- Plugs & Sockets find its applications at air conditioners, welding machines, industrial equipment, etc., are made of non corrosive aluminum alloy
- Conforms to IS 8804



## ENCLOSURES

**NEW**

Description	Modules	Single Door	MRP/Unit in ₹
2-Way	2	DTENC002SD	575
3-Way	3	DTENC003SD	645
4-Way	4	DTENC004SD	645
6-Way	6	DTENC006SD	970

## PLUG & SOCKET DBs

**NEW**

Description	No. of Pins	Modules	Single Door	MRP/Unit in ₹
10A, 2 Pin+SC <sup>^</sup>	P+N	1	DTMPS110SD	1460
20A, 2 Pin+SC <sup>^</sup>	P+N	1	DTMPS120SD	1560
20A, 2 Pin+SC <sup>^</sup>	P+N	2	DTMPS220SD	1700
32A, 3 Pin+SC <sup>^</sup>	3P	3	DTMPS332SD	4030

SC<sup>^</sup> - Scrapping Earth

## METAL PLUG & SOCKET

Description	No. of Pins	Cat No	MRP/Unit in ₹
<b>Metal Plug</b>			
10A, 2 Pin+SC <sup>^</sup>	P+N	MPS210P	320
20A, 2 Pin+SC <sup>^</sup>	P+N	MPS220P	340
20A, 3 Pin+SC <sup>^</sup>	3P	MPS320P	450
32A, 3 Pin+SC <sup>^</sup>	3P	MPS332P	855
<b>Metal Socket</b>			
10A, 2 Pin+SC <sup>^</sup>	P+N	MPS210S	335
20A, 2 Pin+SC <sup>^</sup>	P+N	MPS220S	370
20A, 3 Pin+SC <sup>^</sup>	3P	MPS320S	505
32A, 3 Pin+SC <sup>^</sup>	3P	MPS332S	855

SC<sup>^</sup> - Scrapping Earth

Note: Standard Pack Quantity for Metal Plug & Socket - 20 Nos.



Single Door

Double Door

## HIGHLIGHTS

- Ready to use DBs, complete with colour - coded wire set, 100A bus bar, Neutral bar/s & Earth bar/s
- Superior quality powder coating for better looks and longer life
- DB is suitable for surface or flush mounting



Double Door



Double Door

## SINGLE PHASE NEUTRAL (SPN) DBs

Description	Modules		Single Door	MRP/Unit in ₹	Double Door	MRP/Unit in ₹
	Incomer	Outgoing				
4 way	2	2	BH104SDB	1095	BH104DDB	1750
6 way	2	4	BH106SDB	1200	BH106DDB	1965
8 way	2	6	BH108SDB	1355	BH108DDB	2145
12 way	2	10	BH112SDB	1805	BH112DDB	2615
16 way	2	14	BH116SDB	2250	BH116DDB	3220

## THREE PHASE NEUTRAL (TPN) DBs

Description	Modules		Single Door	MRP/Unit in ₹	Double Door	MRP/Unit in ₹
	Incomer	Outgoing				
4 way	8	4+4+4	BH304SDB	3385	BH304DDB	4375
6 way	8	6+6+6	BH306SDB	4185	BH306DDB	5375
8 way	8	8+8+8	BH308SDB	4835	BH308DDB	6520
12 way	8	12+12+12	BH312SDB	6860	BH312DDB	9380

## PHASE SELECTOR DBs

Description	Modules		Double Door	MRP/Unit in ₹
	Incomer	Outgoing		
4 way	8	4+4+4	BHC04DDB	13775
6 way	8	6+6+6	BHC06DDB	14385

Provided with 40A selector switches

## DY125U & DY250U1 MCCB



Description	Three Pole			Four Pole		
	Current Rating (A)	Cat No	MRP/Unit in ₹	Current Rating (A)	Cat No	MRP/Unit in ₹
MCCB DY125U 16A 10kA FTFM	16	EM909830OBO	3100	16	EM909840OBO	4170
MCCB DY125U 20A 10kA FTFM	20	EM909830OCO	3100	20	EM909840OCO	4170
MCCB DY125U 25A 10kA FTFM	25	EM909830ODO	3100	25	EM909840ODO	4170
MCCB DY125U 32A 10kA FTFM	32	EM909830OEO	3100	32	EM909840OEO	4170
MCCB DY125U 40A 10kA FTFM	40	EM909830OFO	3100	40	EM909840OFO	4170
MCCB DY125U 50A 10kA FTFM	50	EM909830OGO	3100	50	EM909840OGO	4170
MCCB DY125U 63A 10kA FTFM	63	EM909830OHO	3010	63	EM909840OHO	4050
MCCB DY125U 80A 10kA FTFM With Spreader Links	80	EM909830OJO	3390	80	EM909840OJO	4680
MCCB DY125U 100A 10kA FTFM With Spreader Links	100	EM909830OKO	3390	100	EM909840OKO	4680
MCCB DY125U 125A 10kA FTFM With Spreader Links	125	EM909830OLO	4980	125	EM909840OLO	6110
*MCCB DY250U1 160A 10kA FTFM With Spreader Links	160	CM981950OMO	9200	160	CM981960OMO	11900
*MCCB DY250U1 200A 10kA FTFM With Spreader Links	200	CM981950ONO	10300	200	CM981960ONO	13300
*MCCB DY250U1 250A 10kA FTFM With Spreader Links	250	CM981950OPO	13300	250	CM981960OPO	17900

### Key Features

- Conforms to IS/IEC 60947-2, IEC 60947-2 & EN 60947-2
- Range: DY125U- 16A to 125A, 3P/4P  
\*DY250U1- 160A to 250A, 3P/4P
- $I_{cs}=100\%$  of  $I_{cu}$
- High Electrical & Mechanical life
- Thermal Magnetic Release: FTFM - Fixed Thermal Fixed Magnetic  
\*Adjustable overload settings:  $0.8 - 1.0 \times I_n$
- No Load-Line Bias
- ON-TRIP-OFF indication
- Suitable for Isolation
- Common SS enclosure for 3P & 4P

Std Packing of all Cat nos – 1 no

### ACCESSORIES

Description	Std Pack	Cat No	MRP/Unit in ₹
SPREADER TERMINALS- 3P -DY125U	Set of 6	CM977850000	640
SPREADER TERMINALS- 4P -DY125U	Set of 8	CM979210000	1000
Auxiliary/Trip Alarm Contact- 1 C/o - DY125U	1	EM909660000	960
Shunt Release- 110V/240V/415V AC - DY125U	1	EM905200M00	1300
DIRECT ROH- DY125U	1	EM909690000	1850
EXTENDED ROH- DY125U	1	EM909700000	2660
Under Voltage Release - 240V AC - DY125U	1	EM905188000	3910
Size I ENCLOSURE FOR DY125U MCCBs	1	CM909960000	3160
Auxiliary Contact- 1 C/O - DY250U1	1	CM978860000	1450
Auxiliary Contact- 2 C/O - DY250U1	1	CM978870000	2550
Trip Alarm Contact- 1 C/O - DY250U1	1	CM978880000	1450
Trip Alarm Contact- 2 C/O - DY250U1	1	CM978890000	2550
Auxiliary/Trip Alarm Contact- 1 C/o - DY250U1	1	CM978900000	2460
Shunt Release- 24V DC - DY250U1	1	CM914020400	2860
Shunt Release- 110V AC - DY250U1	1	CM978830A00	2860
Shunt Release- 240V/415V AC - DY250U1	1	CM978830M00	2860
Under Voltage Release - 240V AC - DY125U	1	CM97892B000	4740
DIRECT ROH- DY250U1	1	CM980400000	1980
EXTENDED ROH- DY250U1	1	CM980410000	2540
Size II ENCLOSURE FOR DY250U1 MCCBs	1	CM910030000	7260