

POLYCAB IDEAS. CONNECTED.	POLYCAB INDIA LIMITED
PCC LP No. 04/2026-27 Dtd : 8th July 2026	
List of Products Covered in Our PCC LP	
Aluminium Armoured / Unarmoured Cables	
Copper Armoured / Unarmoured Cables	
HT Cables	
1.9 KV / 3.3 KV Cables for Solar	
Instrumentation Cables	
Rubber Cables	
JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables	
RS 485 Cables	
Fire Survival Cables	
FS Aluminium Cables	

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		215	232		256
4		232	273		303
6		291	339		380
10		336	401		525
16	233	390	446		569
25	290	402	535	628	675
35	362	515	732	811	923
50	461	695	948	1081	1217
70	585	886	1272	1473	1651
95	715	1146	1637	1866	2177
120	857	1412	2003	2339	2664
150	1020	1728	2481	2728	3219
185	1238	2110	3069	3451	4055
240	1538	2669	3971	4399	5244
300	1870	3283	4911	5456	6482
400	2414	4303	6232	6923	8334
500	2928	5975	8373	9861	11058
630	3614	7349	10644	12082	14515
800	4496				
1000	5482				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		129	172		207
6		186	233		264
10		254	304		367
16	132	263	353		474
25	158	328	466	598	633
35	205	441	665	719	796
50	280	578	815	957	1050
70	381	790	1150	1322	1505
95	497	1026	1533	1750	2018
120	619	1277	1911	2217	2548
150	776	1598	2403	2682	3171
185	951	1948	2932	3354	3903
240	1209	2489	3771	4276	4995
300	1500	3080	4668	5305	6218
400	1986	4065	6149	6785	8193
500	2460	5854	8206	9663	10837
630	3088	7202	10432	11841	14225
800	3897				
1000	4868				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

FRLS Loading Factor		LSZH	
Cable Size (Sq.mm)	Inner Sheath	Outer Sheath	Inner Sheath
		Unarmd.	
Power (Al.)			
Upto 16	15%	11.5%	22.5%
25 - 50	11.5%	11.5%	18%
70 & above	7.5%	7.5%	22.5%
Power Single Core (Al.)			
Upto 16	-N.A-	15%	-N.A-
25 - 50	-N.A-	15%	-N.A-
70 & above	-N.A-	11.5%	-N.A-

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		499	692	900	1256	1491	1711
6		710	1002	1303	1866	2244	2617
10		1151	1639	2169	2871		
16	1001	1628	2435	3199	4277		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	257	362		14	1208	1996
3	327	481		16	1382	2256
4	411	620		19	1638	2651
5	523	770		24	2049	3339
6	631	903		27	2323	3805
7	657	1050		30	2589	4576
8	747	1211		37	3359	5344
10	936	1438		44	3923	6242
12	1053	1703		61	5776	9050

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH			
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		Armoured				
2 to 4 Core	7.5%	9%	22.5%	22.5%		
5 to 10 Core	7.5%	6%	22.5%	22.5%		
12 & Above	7.5%	6%	18%	18%		

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core		3 Core	4 Core	
	2XY	2XY		2XY	2XY	
4		436		636	839	
6		643		945	1249	
10		1090		1597	2139	
16	883	1598		2405	3170	

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	195	298	14	1114	1911
3	267	420	16	1321	2176
4	350	561	19	1569	2577
5	456	702	24	1959	3254
6	547	824	27	2196	3632
7	582	976	30	2606	4305
8	670	1111	37	3374	5161
10	844	1361	44	3947	6152
12	965	1630	61	5775	8469

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%	
B) Stranding (Upto 6 SQ.MM)	4%	
C) Extruded Innersheath	4%	
D OXYGEN INDEX (FR)	4%	
E) HR PVC Insulation	17.5%	
HR PVC I/S & O/S	7.5% Each	
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%	
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%	
G) PVC Insulated Cables	15%	

FRLS Loading Factor- Control Cable			LSZH		
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%	
5 - 10	7.5%	6%	22.5%	22.5%	
12 & Above	7.5%	6%	18%	18%	

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Glavanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1540	2535	3805	4617	5062	7809
35	2103	3743	5490	6286	7264	10763
50	2945	5053	7407	8721	9899	14799
70	4058	7506	10742	12541	14385	23274
95	5417		15041	17426	19872	
120	6790		18549	22103	24734	
150	8437		22829	26445	30609	
185	10377		28914	33800	38294	
240	13384		37712	43562	50068	
300	16669		48169	55085	63540	
400	22152		62295	69737	86779	
500	27582					
630	34675					
800	43912					
1000	54745					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1451	2466	3717	4522	4958	
35	2014	3661	5395	6176	7145	
50	2860	4961	7302	8603	9768	
70	3993	7389	10609	12402	14230	
95	5172		14888	17260	19698	
120	6525		18380	21907	24542	
150	8159		22656	26236	30396	
185	10055		28688	33556	38050	
240	13017					
300	16256					
400	21663					
500	27060					
630	34087					
800	43259					
1000	54054					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1739				
50		2095				
70	2281	2544				
95	2708	3037	3949	3914	5002	
120	3282	3564	4277	4364	5610	
150	3848	4170	5131	5236	6531	7067
185	4538	4890	5649	5766	7194	7756
240	5808	6219	6758	6895	8281	8767
300	6671	7065	8043	8210	9470	10423
400	8614	9001	9881	10081	11343	11925

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

1 Core HT Cables

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2042	2369	2138	2475	2422	2814	2499	2890	3003	3468	3439	3971
300	2414	2768	2499	2847	2798	3205	2875	3297	3412	4134	3672	4449
400	3050	3373	3099	3424	3437	3815	3526	3895	4070	4790	4305	5075
500	3658	4058	3682	4097	4043	4736	4128	4838	4706	5509	4905	5745
630	4413	4915	4428	4931	4804	5619	4896	5718	5533	6438	5760	6700
800	5368	6210	5387	6243	5800	6710	5905	6827	6568	7572	6853	7897
1000	6515	7515	6526	7515	6986	8015	7078	8143	7805	9400	8390	10144

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%	
2) FRLS PVC Outer Sheath	7.5%	
3) Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 120	663
1 Core x 150	770
1 Core x 185	947
1 Core x 240	1136
1 Core x 300	1434
1 Core x 400	1730
1 Core x 500	2300
1 Core x 630	2813

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 120	1688
3 Core x 150	2069
3 Core x 185	2468
3 Core x 240	3150
3 Core x 300	3829
3 Core x 400	4769

- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	149	0.75	172	1	193	1.5	232	2.5	357
CORE	3	0.5	176	0.75	225	1	253	1.5	329	2.5	465
CORE	4	0.5	208	0.75	265	1	307	1.5	399	2.5	607
CORE	5	0.5	278	0.75	346	1	408	1.5	521	2.5	755
CORE	6	0.5	269	0.75	356	1	429	1.5	549	2.5	872
CORE	7	0.5	340	0.75	434	1	525	1.5	682	2.5	1022
CORE	8	0.5	332	0.75	450	1	541	1.5	707	2.5	1111
CORE	10	0.5	401	0.75	563	1	665	1.5	846	2.5	1356
CORE	12	0.5	451	0.75	630	1	764	1.5	1011	2.5	1675
CORE	14	0.5	571	0.75	733	1	918	1.5	1267	2.5	1900
CORE	16	0.5	608	0.75	807	1	974	1.5	1298	2.5	2051
CORE	19	0.5	704	0.75	935	1	1186	1.5	1603	2.5	2517
CORE	24	0.5	829	0.75	1162	1	1371	1.5	1793	2.5	3176
PAIR	1	0.5	149	0.75	172	1	193	1.5	232	2.5	357
PAIR	2	0.5	226	0.75	289	1	327	1.5	425	2.5	642
PAIR	3	0.5	279	0.75	368	1	440	1.5	564	2.5	882
PAIR	4	0.5	338	0.75	460	1	553	1.5	715	2.5	1128
PAIR	5	0.5	413	0.75	570	1	674	1.5	861	2.5	1377
PAIR	6	0.5	475	0.75	656	1	793	1.5	1040	2.5	1758
PAIR	7	0.5	574	0.75	749	1	934	1.5	1281	2.5	1924
PAIR	8	0.5	609	0.75	841	1	1010	1.5	1322	2.5	2094
PAIR	10	0.5	770	0.75	1014	1	1273	1.5	1733	2.5	2657
PAIR	12	0.5	828	0.75	1176	1	1387	1.5	1907	2.5	3199
PAIR	14	0.5	960	0.75	1330	1	1680	1.5	2342	2.5	3608
PAIR	16	0.5	1094	0.75	1465	1	1899	1.5	2618	2.5	4097
PAIR	19	0.5	1245	0.75	1734	1	2210	1.5	3059	2.5	4801
PAIR	24	0.5	1553	0.75	2233	1	2910	1.5	3722	2.5	5748
TRIAD	1	0.5	184	0.75	226	1	256	1.5	348	2.5	475
TRIAD	2	0.5	321	0.75	419	1	466	1.5	604	2.5	920
TRIAD	3	0.5	463	0.75	583	1	667	1.5	875	2.5	1293
TRIAD	4	0.5	505	0.75	689	1	795	1.5	1031	2.5	1701
TRIAD	5	0.5	646	0.75	857	1	996	1.5	1347	2.5	2003
TRIAD	6	0.5	744	0.75	990	1	1171	1.5	1554	2.5	2355
TRIAD	7	0.5	824	0.75	1098	1	1306	1.5	1750	2.5	2682
TRIAD	8	0.5	879	0.75	1198	1	1354	1.5	1867	2.5	3090
TRIAD	10	0.5	1097	0.75	1498	1	1777	1.5	2446	2.5	3773
TRIAD	12	0.5	1248	0.75	1720	1	2081	1.5	2856	2.5	4464
TRIAD	14	0.5	1420	0.75	1967	1	2381	1.5	3281	2.5	5139
TRIAD	16	0.5	1574	0.75	2191	1	2677	1.5	3717	2.5	5828
TRIAD	19	0.5	1815	0.75	2547	1	3116	1.5	4342	2.5	6834
TRIAD	24	0.5	2247	0.75	3187	1	3894	1.5	5467	2.5	8599
QUAD	1	0.5	215	0.75	279	1	315	1.5	414	2.5	623

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	369	0.75	414	1	405	1.5	487	2.5	789
PAIR	3	0.5	474	0.75	528	1	623	1.5	763	2.5	1076
PAIR	4	0.5	568	0.75	650	1	756	1.5	958	2.5	1326
PAIR	5	0.5	669	0.75	769	1	912	1.5	1121	2.5	1618
PAIR	6	0.5	738	0.75	892	1	974	1.5	1232	2.5	1884
PAIR	7	0.5	844	0.75	987	1	1177	1.5	1487	2.5	2144
PAIR	8	0.5	960	0.75	1091	1	1317	1.5	1686	2.5	2446
PAIR	10	0.5	1132	0.75	1332	1	1604	1.5	2061	2.5	3000
PAIR	12	0.5	1265	0.75	1550	1	1735	1.5	2271	2.5	3433
PAIR	14	0.5	1464	0.75	1743	1	2126	1.5	2747	2.5	4061
PAIR	16	0.5	1647	0.75	1961	1	2384	1.5	3096	2.5	4594
PAIR	19	0.5	1881	0.75	2256	1	2757	1.5	3616	2.5	5371
PAIR	24	0.5	2341	0.75	2835	1	3465	1.5	4560	2.5	6757
TRIAD	2	0.5	457	0.75	525	1	595	1.5	738	2.5	1019
TRIAD	3	0.5	568	0.75	669	1	776	1.5	983	2.5	1392
TRIAD	4	0.5	693	0.75	831	1	962	1.5	1207	2.5	1766
TRIAD	5	0.5	821	0.75	990	1	1164	1.5	1486	2.5	2190
TRIAD	6	0.5	947	0.75	1132	1	1336	1.5	1740	2.5	2571
TRIAD	7	0.5	1048	0.75	1263	1	1499	1.5	1970	2.5	2921
TRIAD	8	0.5	1172	0.75	1451	1	1704	1.5	2247	2.5	3332
TRIAD	10	0.5	1411	0.75	1756	1	2087	1.5	2758	2.5	4142
TRIAD	12	0.5	1633	0.75	2037	1	2436	1.5	3223	2.5	4855
TRIAD	14	0.5	1835	0.75	2316	1	2798	1.5	3718	2.5	5593
TRIAD	16	0.5	2065	0.75	2611	1	3141	1.5	4206	2.5	6348
TRIAD	19	0.5	2392	0.75	3035	1	3687	1.5	4945	2.5	7435
TRIAD	24	0.5	3000	0.75	3820	1	4647	1.5	6179	2.5	9412

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						825	1213	1687	2416
2 Core	185	297	450	680	1161	1821	2775	3735	5314
3 Core	258	425	649	979	1682	2581	3984	5497	7854
4 Core	347	559	851	1291	2207	3407	5230	7228	10392
5 Core	455	763	1169						
6 Core	516	835							
7 Core	582	951							
8 Core	668	1142							
10 Core	851	1419							
12 Core	1002	1676							
14 Core	1161	1944							
16 Core	1317	2211							
19 Core	1597	2597							
24 Core	2034	3298							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	3411	4485	5700	7102	8669	11452	14359	18885	
3 Core	11085	14577	18526	23081	28244	37050	47073	60738	
4 Core	14638	19436	24295	30370	37111	48894	61118	80478	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	168	261				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	220	338	596	1319	2517	4620

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	192	368	570			

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	206
	22 AWG	0.32	233
	20 AWG	0.50	250
	18 AWG	0.80	300
	17 AWG	1.00	333
2 Pair	24 AWG	0.205	309
	22 AWG	0.32	341
	20 AWG	0.50	356
	18 AWG	0.80	488
	17 AWG	1.00	547

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	138
	22 AWG	0.32	159
	20 AWG	0.50	176
	18 AWG	0.80	227
	17 AWG	1.00	255
2 Pair	24 AWG	0.205	214
	22 AWG	0.32	255
	20 AWG	0.50	288
	18 AWG	0.80	385
	17 AWG	1.00	441

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	231
	22 AWG	0.32	261
	20 AWG	0.50	280
	18 AWG	0.80	336
	17 AWG	1.00	373
2 Pair	24 AWG	0.205	346
	22 AWG	0.32	382
	20 AWG	0.50	399
	18 AWG	0.80	547
	17 AWG	1.00	613

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	155
	22 AWG	0.32	178
	20 AWG	0.50	197
	18 AWG	0.80	254
	17 AWG	1.00	286
2 Pair	24 AWG	0.205	240
	22 AWG	0.32	286
	20 AWG	0.50	323
	18 AWG	0.80	431
	17 AWG	1.00	494

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	375	431		544
2.5	498	677		765
4	672	876		957
6	840	1216		1440
10	1241	1836		2166
16	1746	2672		3300
25	2520	3871	4398	4839
35	3420	5281	6000	6651
50	4695	6936	7801	8970
70	6450	9973	10951	13051
95	8881	13651	14851	17551
120	13801	17266	18902	22201

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	418	476		595
2.5	549	733		821
4	733	939		1017
6	899	1288		1515
10	1312	1918		2251
16	1821	2758		3407
25	2614	3981	4517	4962
35	3524	5407	6134	6792
50	4816	7072	7945	9136
70	6596	10153	11136	13259
95	9062	13850	15059	17787
120	14035	17490	19152	22486
Page 16 of 18				

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

				Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	434	499		622
2.5	568	763		855
4	757	969		1057
6	922	1327		1565
10	1341	1966		2312
16	1856	2822		3481
25	2673	4076	4630	5081
35	3593	5513	6263	6931
50	4908	7213	8108	9318
70	6717	10343	11349	13510
95	9194	14066	15307	18061
120	14241	17756	19454	22831
				Page 17 of 18

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables

Sq.mm.	3 Core	4 Core
16	591	755
25	816	1028
35	1004	1279
50	1251	1622
70	1670	2172
95	2058	2660
120	2481	3246
150	2985	3881
185	3645	4740
240	4606	5998
300	5588	7309
400	7025	9175